

General Doors – Advantage Product Overview

General's Advantage Door is a three layer product, made with a 1-3/8" thick polystyrene core sandwiched between two 26-gauge pre-finished steel skins with a thermal break. The steel is protected by a G60 galvanizing layer topped by a heavy duty two-coat baked-on polyester paint system. The rated R-value is 6.7 and the door is available in four colors: White, Almond, Brown, and Sandtone. This door is used by custom home builders and is a very popular replacement door.

- [Sandwich-type construction with 1-3/8" polystyrene insulation, pressure bonded between two skins of 26 gauge (.017) G60 steel

- [Steel is rust-proofed with hot dipped galvanizing, pre-painted on both sides with a primer, and finished with a top coat of baked on polyester for an exterior paint thickness of 1.0 mil

- [Three layer construction provides a calculated insulation value of R-6.7, along with exceptional strength and substantial, solid feel during operation

- [Finely detailed wood grain surface with deeply embossed panels for sharp, well-defined appearance

- [Raised panel sizes of appropriate proportions and spacing ensure all door sizes have an authentic raised panel look

- [Double tongue and groove joint for the tightest section fit possible

- [Thermal break between steel skins

- [Also available in a flush version

- [Heavy duty hardware and commercial grade 14 gauge full leaf hinges are standard

- [Three year hardware warranty